



Technical specifications	
Function	ON/OFF
Cable length [m]	6
Weight [kg]	0,1
IP rating	IP21
Operating temperature [°C]	-40 to +55
Storage temperature [°C]	-50 to +85
H/W/D [MM]	32/40/40

Remote control

Item number: 709340

Remote control

Remote control for use with DEFA inverters

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Installation

The remote control is fastened with the attached adhesive tape. Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician.

Read the mounting and user guide carefully.

Use

1. Set the control switch on the inverter to either ON or ECO
2. Use the remote control to turn on or off the inverter

NOTE: If the control switch on the inverter is in OFF position the remote control will not work.

The remote control is used to control the new black series of inverters from DEFA. It switches the inverter ON or OFF. If the inverter is equipped with an eco-mode function this will have to be preset on the inverter to be used. This is not changeable from the remote control. The green light on the remote control will light up when the inverter is turned on.

Maintenance

Must be kept dry. Clean with freshwater, dry cable and contacts, and spraycontact pins with lubricant suitable for cleaning and lubrication of electric material if necessary. The remote control is maintenance free.