



H

W

H = Height, W = Width, D = Depth



Technical specifications

Input voltage [VAC]	230
Rated power [W]	632
Operating temperature [°C]	-35/+50
Charging voltage* [VDC]	14,4
Maintenance charging [VDC]	13,6
Charging current [A]	2x20
Battery size, max [Ah]	2x300
IP rating [IP]	44
H/W/D [mm]	183x190x53
Weight [kg]	3
Protection class	1
Certifications	EN60335-1, EN60335-2-29, EN55014-1, EN55014-2, EN61003-3/2

* Temperature-compensated approx 5,0 mV/°C/cell. Ref. 25°C.



SCAN ME
defa.com

MultiCharger 2x20

Item number: 705900

MultiCharger 2x20

DEFA MultiCharger 2x20A is based on modern switchmode technology. This charger represents the latest technology within battery charging and will give the batteries optimum life.

It is well suited to battery sizes up to approx. 2x300Ah and can maintenance charge the battery for an unlimited time.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician. Read the mounting and user guide carefully.

Use

The charger can stand parallel current load up to 17A pr. channel from another user at the same time as it charge the battery. The charging voltage is temperature compensated with external sensor. The charger can be connected to a LED remote gauge.

LED

Green pulse - Charging, Green light - Fully charged, Red pulse - Error

Maintenance

The charger is maintenance free.

